

## For saws / Circular Saw Blades

### DART Reducing Ring

Quality reducing rings to ensure that blades fit different - accurately machined with reamed bores and splined outside edges for precision fit. Must be inserted correctly; pressed or glued into the body of the blade. Do not use a reducing ring when the saw flange is not more than 5mm diameter bigger than the original saw blade bore size.



#### General Information

|                                   |             |
|-----------------------------------|-------------|
| Quality                           | Standard    |
| Outer Box Qty.                    | 1           |
| Colour Description                | Silver      |
| Diameter Description (mm)         | 20          |
| Pallet Qty.                       | 1           |
| Plate Description (mm)            | 1.1         |
| Size Description (mm)             | 20mm x 16mm |
| Package Length (cm)               | 7           |
| Designed To Cut                   |             |
| Package Width (cm)                | 0.1         |
| Package Height (cm)               | 6.2         |
| Outside Diameter Description (mm) | 20          |
| Inside Diameter Description (mm)  | 16          |
| Thickness (mm)                    | 1.1         |
| Pack Size Description             | Pk 1        |
| Item Length (cm)                  | 2           |
| Item Width (cm)                   | 1.1         |
| Item Height (cm)                  | 2           |
| Net Weight (kg)                   | 0.005       |

Gross Weight (kg)

0.005

---